




Remedy Optimization via Correlation of Hydraulic Profile Tooling and Membrane Interface Probe Studies



NASA, Kennedy Space Center – Michael J. Deliz, PG

Tetra Tech – Christopher A. Hook, PE, Steven H. Ruffing, PE, Mark P. Speranza, PE



Kennedy Space Center
Center Operations Directorate


Goals / Overview



TETRA TECH

- ◆ Site Background
- ◆ Interim Measure (IM) Results
- ◆ Hydraulic Profiling Tool (HPT)/
Membrane Interface Probe
(MIP) Study Goals
- ◆ Study Data
 - Pre-IM/Interim IM MIP data
 - MIP/HPT Data Correlation
- ◆ Refined Conceptual Model
- ◆ Optimizations








Kennedy Space Center
Center Operations Directorate


Adaptive Management Perspective



- ◆ LC34 Adaptive Site management Practices (Battelle 2012):
 - Assessment (*DOES NOT END WITH DESIGN*)
 - Design (*DOES NOT END WITH IMPLEMENTATION*)
 - Optimization Evaluations (*THROUGHOUT*)










Kennedy Space Center
Center Operations Directorate

Pre-IM Site Conceptual Model



- DNAPL (TCE) present between 18 ft & 80 ft bls




Kennedy Space Center
Center Operations Directorate

Interim Measure Overview



- ◆ Hydraulic control of the DNAPL source zone and deep groundwater TCE plume >300 µg/l
- ◆ Treat extracted groundwater to GCTLs
- ◆ Design peak flow of 50 gpm and normal flow of 39 gpm
- ◆ Primary components include:
 - 3 shallow recovery wells
 - 6 deep recovery wells
 - Primary treatment via air stripping
 - Liquid Phase GAC polishing
 - Catalytic oxidation off gas treatment
 - Discharge treated groundwater to 12 deep injection wells and infiltration gallery






Kennedy Space Center
Center Operations Directorate




TETRA TECH

Interim Measure Results

- ◆ CVOC Mass recovery: 38,294 lb (4/2014); 16 lb/d average (Year 4)
- ◆ Cost per pound of CVOC mass recovered: \$83/lb (Previous Year: \$94/lb)
 - Capital cost driven, figure continues to decrease as operation continues
- ◆ Groundwater recovery: 61M gallons (4/2014)





Kennedy Space Center
Center Operations Directorate

MIP/HPT Study Goals



- ◆ Identify depth intervals where contamination persists
- ◆ Obtain knowledge of hydraulic conductivity variations
- ◆ Correlate conductivity and contamination magnitude
- ◆ Distinguish mass storage and transport zones
- ◆ Optimize existing operations and IM expansion efforts






Kennedy Space Center
Center Operations Directorate

HPT Overview



TETRA TECH


- ◆ Technology use: Real-time vertical hydraulic conductivity profiling
- ◆ Equipment: DPT Rig, HPT Tooling (pressure/conductivity sensor & water injector)
 - Water injected as tool is advanced
 - Pressure sensor measures response of soil to water injection
 - Identifies ability of soil to transmit water
- ◆ Measured data output: Electrical conductivity, injection flow and pressure
- ◆ K value calculated by HPT software
 - Peaks indicate high K/flow zones
 - Valleys indicate low K/flow zones





Kennedy Space Center
Center Operations Directorate

MIP/HPT Locations





Kennedy Space Center
Center Operations Directorate


RW1A/1B Optimization:



Pre-IM MIP:

Jan 2013 MIP:


Jan 2013 HPT/MIP



Well Screen

Optimization

Pump Intake



RW-1A Influent

Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	240,000	20.9
2/21/2011	35,700	6.2
2/2/2012	85,000	7.0
3/11/2013	91,900	6.8
4/3/2014	91,800	6.7

RW-1B Influent

Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	130,000	5.4
2/21/2011	198,000	7.4
2/2/2012	176,000	13.2
3/11/2013	73,800	4.8
4/3/2014	62,400	6.1

*Increase RW1B from 5 to 7.5 gpm 12



Kennedy Space Center
Center Operations Directorate




RW2A/2B Optimization



Pre-IM MIP:

Jan 2013 MIP:

Jan 2013 HPT/MIP:



RW-2A Influent		
Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	280,000	28.5
2/21/2011	3,630	4.4
2/2/2012	42,500	3.8
3/11/2013	39,000	3.2
4/3/2014	33,600	2.6

RW-2B Influent		
Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	940,000	34.7
2/21/2011	203,000	7.4
2/2/2012	126,000	9.3
3/11/2013	66,300	4.2
4/3/2014	59,900	5.6

*Increase RW2B from 5 to 7.5 gpm 13





Kennedy Space Center
Center Operations Directorate



RW3A/3B Optimization

Jan 2013 HPT/MIP:




RW3A

- Mobile mass at 30-46' bls
- Immobile mass at 43-52' bls (within screen)
- Isolate screen from 30-46' bls

RW3B

- Immobile mass at 43-52' bls
 - Mobile mass at 52-65' bls
 - Move pump intake to 65' bls; pump at 3 gpm
- *Rehab (surge/chemical) if no signif. changes
- *Layer 4 mass storage



RW-3A Influent		
Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	41,000	3.8
2/21/2011	3,520	2.9
2/2/2012	427	1.8
3/11/2013	80	0.5
4/3/2014	<60	0.4

RW-3B Influent		
Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	16,000	1.0
2/21/2011	6,540	0.3
2/2/2012	3,210	0.1
3/11/2013	2,200	0.1
4/3/2014	2,200	0.1



Kennedy Space Center
Center Operations Directorate


RW4B Optimization



Pre-IM MIP:

Jan 2013 MIP:

Jan 2013 HPT/MIP:



Well Screen

Optimization

Packer



RW-4B Influent

Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	250,000	17.0
2/21/2011	54,100	3.5
2/2/2012	16,100	1.0
3/11/2013	2,640	0.2
4/3/2014	517	<0.1

*Reduce flow rate from 4 to 3 gpm
(expansion flow budget variable)



Kennedy Space Center
Center Operations Directorate




RW5B Optimization



Pre-IM MIP:

Jan 2013 MIP:

Jan 2013 HPT/MIP:



Well Screen
Optimization
Packer



RW-5B Influent		
Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	250,000	16.9
2/21/2011	86,400	5.6
5/18/2011	77,700	5.0
2/2/2012	57,000	3.7
3/11/2013	47,300	3.1
4/3/2014	9,050	0.6

*Reduce flow rate from 4 to 2 gpm
(expansion flow budget variable)





Kennedy Space Center
Center Operations Directorate

RW6B Optimization



Pre-IM MIP:

Jan 2013 MIP:



RW-6B Influent		
Date	TCE (ppb)	Mass Recovery (lbs/d)
1/20/2010	270,000	18.5
2/21/2011	43,400	3.0
2/2/2012	9,320	0.6
3/11/2013	1,360	0.1
11/20/2013	<0.21	<0.1

*Based on influent and MIP data, shutoff of well approved; pumping capacity offset to other wells



Kennedy Space Center
Center Operations Directorate

Conceptual Model Refinement




- ◆ Additional TCE mass identified between DPT sampling intervals +/- 18 feet bls in lower portion of Layer 1
- ◆ MIPS/HPTs confirmed Layer 4 mass storage extent
- ◆ MIPS improved understanding of flux and remaining source zones
- ◆ MIPS verified source zone model assumptions
- ◆ HPTs identified that Layer 6 (60-80 feet bls) is more heterogeneous than identified via soil coring
- ◆ MIP/HPT pairings narrowed the intervals capable of mass transport and storage within Layer 6
- ◆ MIP/HPT pairings hint at mass storage/back diffusion in upper portion of Layer 7 (>80 ft bls)



Kennedy Space Center
Center Operations Directorate

Conceptual Model Refinement






Kennedy Space Center
Center Operations Directorate


Recovery Well Influent




Shallow Zone TCE Results



Deep Zone TCE Results





Kennedy Space Center
Center Operations Directorate

Remedial Strategy Refinement



- ◆ MIP/HPT pairings provided additional lines of evidence for capture/flow manipulation
- ◆ Recovery well screens selectively packered
- ◆ Pump intakes adjusted based on contaminant magnitude and conductivity characteristics
- ◆ RW-6B deactivated based on multiple criteria, supported by Pre-IM and Interim MIP data
- ◆ Identified need for additional deep extraction well (via MIP)
- ◆ Upcoming expansion of shallow recovery well network enhanced with increased site knowledge



Kennedy Space Center
Center Operations Directorate

Applying to Your Site



- ◆ Enhance site conceptual model/remedy approach
- ◆ Verify sampling intervals relative to conductivity zones
- ◆ Does the remedy address mobile/immobile mass?
- ◆ Does hydraulic conductivity constrain the effectiveness?
- ◆ HPT/MIP assessment is not technology specific. Examples:
 - Surgical treatment interval optimization
 - Substrate distribution prediction
 - Injection pressure requirements
 - Remedy progress/optimization
 - Mobile/immobile mass assessment
 - Changes in permeability from remedy (e.g., mixing, ZVI, etc.)

Questions

